SNLP assignment 3: Language identification Deadline: Jun 13, 2018 @ 10:00 CEST

In this set of exercises, we will train a language identifier using the corpora we built collaboratively in the first exercise set. Our aim is to identify the language of a given text. Language identification is generally considered as a 'mostly solved' problem, although interesting issues remain with closely-related languages and multi-lingual texts (e.g., including code-switching).

For the sake of exercise, we will build relatively 'dumb' models in this assignment. Particularly, the features you are asked to use are not ideal (though not too bad either) for the task at hand. You are encouraged to try better models/methods in Exercise 7, but, otherwise, please follow the instructions closely for the submitted assignment.

General instructions

This assignment consists of seven exercises. Your solutions should include a single Python script (download-tweets.py) and a CSV-formatted data file (tweet-corpus.csv) for Exercise 1. Please create a single Python script, language-detect.py, for exercises 2 through 6.

For Exercise 7, you can create as many additional code/data files as you need (or alternatively use the results from Exercise 6 without further effort). However, the requirement is a single data file predictions.csv, which contains the predicted language codes from your best model.

Exercises

Exercise 1. Gather your data

A subset of the tweet IDs collected by the each participant of Assignment 1 is provided in your assignment repository. Write a python script, download-tweets.py that

- takes a list of file names as in our data set from the *command line*¹
- downloads the tweets with the ids
- writes a single comma-separated-value (CSV) file with the name tweet-corpus.csv where the first column is the three-letter language code, second column is the tweet id, and the last column is the tweet text²

Exercise 2. Feature extraction

Write a Python function that³

- reads the CSV file created in Exercise 1
- counts the number of character bigrams in each document,

Why am I doing this?

- Experiment with classification using a real NLP application
- A first, practical exposure to n-grams and *bag-of-words* (or bag of n-grams) representation
- Experiment with regularization and model selection

All source code and data files must be pushed to your assignment repository before the deadline.

¹ Although we will only use this fixed data set in this exercise, your code should be able to handle any file list given on the command line.

² You are recommended to use a library, e.g., Python csv library, for writing (and later reading) the data.

³ **Do not use** sklearn 'vectorizer' models in this exercise. Although, this exercise takes only a few lines to solve using sklearn.feature_extraction.text .CountVectorizer, you are required to implement it yourself for the sake of exercise.

- and returns a tuple containing:
 - a matrix whose rows correspond to the tweets, and columns correspond to the every bigram that occurs in the data set⁴
 - associated language codes

Exercise 3. Logistic regression

Train a Logistic regression classifier (using sklearn.linear_model. LogisticRegression) on the complete data set created in Exercise 2. Print out the accuracy of your model on the training set using

score() method of the model.

Exercise 4. Precision, recall, F-score

- Write a function that takes two sequences (gold-standard labels and predicted labels) and a label (language code), and returns the precision, recall, and F1-score with respect to the given label.⁵
- Print out *macro averaged* precision, recall, and F1-score of the model trained in Exercise 3 on the training set.

Exercise 5. K-fold CV

Implement a function that performs k-fold validation.⁶

Using your function, output the mean of the macro-averaged precision, recall and F1-score over 5-fold cross validation.

Exercise 6. Model selection

The model we studied here is rather simple, it has a single hyperparameter, the regularization constant.

Tune your model, searching the value of the hyperparameter that yields the best macro-averaged F1-score. Output the value of the hyperparameter as well as the precision, recall and F1-score obtained with it.

Exercise 7. A challenge

Tune a classifier that would achieve the best macro-averaged F1-score with the given training set. For this exercise, you can use any classification algorithm, or any features that you can extract from the given training set.⁷

You will be required to produce predictions on a test set that will be released the day before the deadline. The test data for this exercise will be in the same format as the CSV file, except the language codes and tweet IDs will be replaced by an underscore. A sample test set file is provided as testset-sample.csv in your assignment repository. The output file (predictions.csv) should be in the same format, but include the language codes as the first field of the CSV file. Further instructions will be provided together with the real test data.

The teams with the best scores (if statistically not different from the best score) will receive and additional bonus point. ⁴ You may want to use a sparse matrix implementation from scipy package in case you encounter memory issues.

⁵ Again, **do not use** the implementation from sklearn.metrics package, but implement the function yourself.

⁶ Yet again, do not use the implementation from sklearn.model_selection package, but implement the function yourself.

⁷ The use of external resources are not allowed. Your model should be tuned and tested only on the data provided (you can also use the sample gold-standard data set from the file testset-sample+gold.csv for tuning in the previous and current exercise).

You are also recommended to stick to the classifiers implemented in the sklearn package.